



# SAFETY DATA SHEET

Page : 1

Revised edition no : 0

Date : 3 / 1 / 2011

Supersedes : 0 / 0 / 0

**Strizo PU 380 TR.****550 TR A**

Xn : Harmful



3 : Flammable liquid.

**Producer**

Strizo synthetics B.V.  
Jules Verneweg 98  
5015 BM Tilburg Nederland  
Tel: 0031 (0) 13-5362885 Fax: 0031 (0) 13-5427195  
E - Mail: info@strizo.com Web Site : www.strizo.com

**Responsible for distribution**

Strizo synthetics B.V.  
Jules Verneweg 98  
5015 BM Tilburg Nederland  
Tel: 0031 (0) 13-5362885 Fax: 0031 (0) 13-5427195  
E - Mail: info@strizo.com Web Site : www.strizo.com

**1 IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING****Use** : Industrial.**2 COMPOSITION / INFORMATION ON INGREDIENTS****Components** : This product is hazardous.

Substance name	Contents	CAS No	EC No	Index No	Classification
Xylene	: 10 - 25	1330-20-7	215-535-7	601-022-00-9	----- R10 Xn; R20/21 Xi; R38
Ethylbenzene	: 1 - 5	100-41-4	202-849-4	601-023-00-4	----- F; R11 Xn; R20
n-Butyl acetate	: 50 - 100	123-86-4	204-658-1	607-025-00-1	----- R10 R66 R67
2-Butanol	: 0.1 - 0.5	78-92-2	201-158-5	603-127-00-5	----- R10 R67 Xi; R36/37
2-methoxy-1-methylethyl acetate	: 5 - 10	108-65-6	203-603-9	607-195-00-7	----- R10 Xi; R36

**3 HAZARDS IDENTIFICATION**

**Risk Phrases** : This product is flammable.  
Harmful if swallowed.

- Inhalation : Vapours may cause drowsiness and dizziness.

- Skin contact : Prolonged or repeated contact may cause skin to become dry or cracked.

**4 FIRST AID MEASURES**

- Inhalation : Remove victim to fresh air.  
If you feel unwell, seek medical advice (show the label where possible).

- Skin contact : Wash skin with mild soap and water.

- Eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking, tears or redness persist.

- Ingestion : Do not induce vomiting.  
Give water to drink.  
Call a physician immediately.

**5 FIRE-FIGHTING MEASURES**

**Flammable class** : This product is flammable.

**Extinguishing media** : Powder.  
Foam.

**Strizo synthetics B.V.**

Jules Verneweg 98 5015 BM Tilburg Nederland  
Tel: 0031 (0) 13-5362885 Fax: 0031 (0) 13-5427195  
E - Mail: info@strizo.com Web Site : www.strizo.com

**In case of emergency : 0031 (0) 13-5362885**



# SAFETY DATA SHEET

Page : 2

Revised edition no : 0

Date : 3 / 1 / 2011

Supersedes : 0 / 0 / 0

**Strizo PU 380 TR.****550 TR A**

## 5 FIRE-FIGHTING MEASURES (continued)

Protection against fire : Water spray.  
: Wear proper protective equipment.

## 6 ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear recommended personal protective equipment.  
Environmental precautions : Prevent entry to sewers and public waters.  
Clean up methods : Dispose in a safe manner in accordance with local/national regulations. Clean up any spills as soon as possible, using an absorbent material to collect it.

## 7 HANDLING AND STORAGE

General : Ventilate confined spaces before entering.  
Precautions in handling and storage : Avoid all unnecessary exposure.  
Handling : Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work.  
Keep away from food, drink and animal feeding stuffs.

## 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection : Wear suitable hand, body and head protection. Wear goggles with suitable filter lenses when use is cutting/welding.  
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment.  
- Hand protection : Wear suitable gloves resistant to chemical penetration.  
- Eye protection : Safety glasses with side guards should be worn to prevent injury from airborne particles and/or other eye contact with this product.  
- Ingestion : When using, do not eat, drink or smoke.  
Occupational Exposure Limits : n-Butyl acetate : OEL (UK)-LTEL [ppm] : 150  
n-Butyl acetate : OEL (UK)-STEL [ppm] : 200  
Ethylbenzene : OEL (UK)-LTEL [ppm] : 100  
Ethylbenzene : OEL (UK)-STEL [ppm] : 125  
2-Butanol : OEL (UK)-LTEL [ppm] : 100  
2-Butanol : OEL (UK)-STEL [ppm] : 150

## 9 PHYSICAL AND CHEMICAL PROPERTIES

Physical state at 20 °C : Liquid.  
Physical state : Liquid.  
Colour : Colourless.  
Odour : Solvent.  
Boiling point [°C] : ca 127  
Density [kg/m<sup>3</sup>] : ca 1,04 g/m<sup>3</sup> bij 20 gr.  
Vapour pressure, 20 °C : ca 12 mbar  
Viscosity at 25 °C [mPa.s] : 2.500 mPa.s  
Solubility in water : Insoluble.  
Flash point [°C] : 30 gr celcius  
Explosion limits - lower [%] : 1.2

### Strizo synthetics B.V.

Jules Verneweg 98 5015 BM Tilburg Nederland  
Tel: 0031 (0) 13-5362885 Fax: 0031 (0) 13-5427195  
E - Mail: info@strizo.com Web Site : www.strizo.com

In case of emergency : 0031 (0) 13-5362885



# SAFETY DATA SHEET

Page : 3

Revised edition no : 0

Date : 3 / 1 / 2011

Supersedes : 0 / 0 / 0

**Strizo PU 380 TR.****550 TR A**

## 9 PHYSICAL AND CHEMICAL PROPERTIES (continued)

Explosion limits - upper [%] : 8.0

## 10 STABILITY AND REACTIVITY

Hazardous reactions : None under normal conditions.

Hazardous properties : None under normal conditions.

## 11 TOXICOLOGICAL INFORMATION

Acute toxicity : No known toxicological effects from this product.

- Dermal : May cause sensitization by skin contact.

- Ocular : Irritating to eyes.

## 12 ECOLOGICAL INFORMATION

Ecological effects information : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Environmental precautions : Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

## 13 DISPOSAL CONSIDERATIONS

General : Dispose in a safe manner in accordance with local/national regulations. Dispose of this material and its container at hazardous or special waste collection point.

## 14 TRANSPORT INFORMATION

UN No. : 1866

- ADR Class : 3

- Packing group : III

## 15 REGULATORY INFORMATION

- Symbol(s) : Xn : Harmful

- R Phrase(s) : R10 : Flammable.  
R20/21 : Harmful by inhalation and in contact with skin.  
R36/37/38 : Irritating to eyes, respiratory system and skin.  
R66 : Repeated exposure may cause skin dryness or cracking.

- S Phrase(s) : S36/37 : Wear suitable protective clothing and gloves.

Contains : n-Butyl acetate - Xylene - 2-methoxy-1-methylethyl acetate - Ethylbenzene - 2-Butanol

## 16 OTHER INFORMATION

List of relevant R phrases (heading 2) : R10 : Flammable.  
R11 : Highly flammable.  
R20 : Harmful by inhalation.  
R20/21 : Harmful by inhalation and in contact with skin.  
R36 : Irritating to eyes.  
R36/37 : Irritating to eyes and respiratory system.  
R38 : Irritating to skin.  
R66 : Repeated exposure may cause skin dryness or cracking.**Strizo synthetics B.V.**

Jules Verneweg 98 5015 BM Tilburg Nederland

Tel: 0031 (0) 13-5362885 Fax: 0031 (0) 13-5427195

E - Mail: info@strizo.com Web Site : www.strizo.com

**In case of emergency : 0031 (0) 13-5362885**



# SAFETY DATA SHEET

Page : 4

Revised edition no : 0

Date : 3 / 1 / 2011

Supersedes : 0 / 0 / 0

**Strizo PU 380 TR.****550 TR A****16 OTHER INFORMATION (continued)**

R67 : Vapours may cause drowsiness and dizziness.

The contents and format of this SDS are in accordance with EEC Commission Directive 2001/58EC.

**DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

**End of document****Strizo synthetics B.V.**

Jules Verneweg 98 5015 BM Tilburg Nederland

Tel: 0031 (0) 13-5362885 Fax: 0031 (0) 13-5427195

E - Mail: [info@strizo.com](mailto:info@strizo.com) Web Site : [www.strizo.com](http://www.strizo.com)**In case of emergency : 0031 (0) 13-5362885**